

Temperature probe Pt1000TG8/M, MiniDin connector, cable 15 meters

code: SN118M

Multi-purpose watertight IP67 temperature probe -80 to +200°C.

The probe is designed to measure the temperature of gaseous and liquid substances. Used type of lead-in cable has silicone insulation and shielding.



The probe is designed for universal use, the method of use must be chosen with regard to the temperature and chemical resistance of the case and lead-in cable.

Technical data

TEMPERATURE SENSOR	
Measuring range	-50 to +200 °C -80 to +200 °C (for static position of lead-in cable)
Accuracy	± (0.15 + 0.002 t) at °C
Accuracy class	A
Time response	t0.5 <7 s (in flowing water at > 0.2 m/s) t63 <10s, t95 <30s (in liquid) t63 <60s, t95 <150s (air flow 1m/s)
Type of sensing element	Pt1000
Temperature coefficient	3850 ppm / °C
GENERAL TECHNICAL DATA	
Wire connection	2-wire connection
Material of the case	stainless steel DIN 1.4301
Dimensions of the case	length 40 mm; diameter 5.7 ± 0.1 mm
Lead-in cable	silicone shielded
Length of lead-in cable	15 meters
Connector	MiniDin
IP protection	IP67
Warranty	30 months