

# IoT Wireless Four channel Datalogger with pulse and two-state inputs, with built-in 4G modem and Flat Rate SIM Card

code: U7844Gsim



IoT Wireless Datalogger kit with built-in GSM modem and Flat Rate SIM Card allows the instant connection to the COMET Cloud.

IoT Datalogger is designed to record from four binary inputs or from two pulse and two binary inputs. In case of exceeded set limits e-mail is sent from the [COMET Cloud](#).

Alarms are also indicated locally by LED, LCD and acoustically by built-in beeper.

The recording is performed in a non-volatile electronic memory. The data can be transferred to a PC via included USB-C cable.

GSM recorder **includes Traceable calibration certificate** with declared metrological traceability of etalons is based on requirements of **EN ISO/IEC 17025 standard**.

## Technical data

|  |  |
|--|--|
| BINARY INPUT                                 |  |
| Parameters of the voltage contact            | „L“ level input voltage: < 0,4 V(*); „H“ level input voltage: > 2 V; Minimum voltage applicable: 0 V; Maximum voltage applicable: +30 V DC   |
| Parameters of the voltage-free contact       | Contact resistance in „switched-on“ state: < 10 kOhm; Contact resistance in the „switched-off“ state: > 300 kOhm; Contact voltage in the „switched-off“ state: ca 3 V; Minimum state duration necessary for latching the state: 1s |
| COUNTER INPUT                                |  |
| Counter parameters                           | Range 24 bits (16 777 215), possibility of letting the counter overflow  |
| Maximum pulse frequency                      | configured for voltage input - max. 5kHz<br>configured for a voltage-free or open-collector transistor - max. 200Hz  |
| GSM MODEM PARAMETERS                         |  |
| LTE Cat 1                                    | LTE FDD/GSM/GPRS/EDGE  |
| Supported network types                      | GSM/GPRS/EDGE 900/1800 MHz<br>LTE FDD B1/B3/B5/B7/B8/B20   |
| GENERAL TECHNICAL DATA                       |  |
| Operating temperature                        | -20 to +60 °C  |
| Channels                                     | 4x binary input nebo 2x binary input a 2x counter  |
| Memory                                       | 500,000 values in noncyclic logging mode; 350,000 values in cyclic record mode   |
| Recording interval to the internal memory    | adjustable from 1 second to 24 hours   |
| Recording interval to the COMET Cloud        | from 5 minutes   |
| Interval for measuring and evaluating alarms | adjustable 1 s, 10 s, 1 min  |

|                              |  |
|------------------------------|--|
| Recording mode               | noncyclic - data logging stops after filling the memory<br>cyclic - after filling memory oldest data is overwritten by new |
| Real time clock              | year, leap year, month, day, hour, minute, second  |
| Power                        | rechargeable Li-Ion battery A8200, 3.6V/5200mAh  |
| Protection class             | IP20   |
| Dimensions                   | 61 x 93 x 53 mm, with antenna 120 x 93 x 53 mm   |
| Weight (including batteries) | approx. 270 g  |
| Warranty                     | 3 years  |