

# IoT Wireless CO2 datalogger with built-in sensor, 4G modem and Flat Rate SIM Card

code: U8410Gsim



IoT Wireless Datalogger kit with built-in GSM modem and Flat Rate SIM Card allows the instant connection to the COMET Cloud. IoT Datalogger is designed to record CO2 from built-in sensor. In case of exceeded set limits e-mail is sent from the [COMET Cloud](#).

Alarms are also indicated locally by LED, LCD and acoustically by built-in beeper.

The recording is performed in a non-volatile electronic memory. The data can be transferred to a PC via included USB-C cable.

GSM recorder **includes Traceable calibration certificate** with declared metrological traceability of etalons is based on requirements of **EN ISO/IEC 17025 standard**.

## Possibility to [extend the measuring range](#) for an additional charge:

- Measuring range: 0 to 10 000 ppm
- Accuracy: 100 ppm + 5% of the measured value at 25 °C and 1013 hPa

## Technical data

CO2 SENSOR	
Measuring range	0 to 5000 ppm
Accuracy	±(50 ppm +3% from reading)
Measurement interval	15 s with external power supply, 2 min on battery power
GSM MODEM PARAMETERS	
LTE Cat 1	LTE FDD/GSM/GPRS/EDGE
Supported network types	GSM/GPRS/EDGE 900/1800 MHz  LTE FDD B1/B3/B5/B7/B8/B20
GENERAL TECHNICAL DATA	
Operating temperature	-20 to +60 °C
Channels	internal CO <sub>2</sub> sensor
Memory	500,000 values in noncyclic logging mode; 350,000 values in cyclic record mode
Recording interval to the internal memory	adjustable from 1 second to 24 hours
Recording interval to the COMET Cloud	from 5 minutes
Interval for measuring and evaluating alarms	adjustable 1 s, 10 s, 1 min
Recording mode	noncyclic - data logging stops after filling the memory cyclic - after filling memory oldest data is overwritten by new
Real time clock	year, leap year, month, day, hour, minute, second
Power	rechargeable Li-Ion battery A8200, 3.6V/5200mAh
Protection class	IP20
Dimensions	61 x 93 x 53 mm, with antenna 120 x 93 x 53 mm

Weight (including batteries)	approx. 250 g
Warranty	3 years