

IoT wireless thermometer with three-channels, LoRaWAN network

code: W0932



The W0932 sensor with LoRaWAN network output measures temperature from the built-in sensor and from two external Pt1000 probes on the cable and can be installed directly in the measured environment thanks to its IP65-rated enclosure. LoRa devices are powered by a replaceable battery with a lifespan of up to 10 years (3 years standard). External power with optional accessories is also available.

Measured values are transmitted wirelessly at adjustable intervals (from 5 minutes to 24 hours) to the COMET Cloud storage, where they are accessible to users via computer or mobile device. The sensors offer remote configuration from the COMET Cloud and feature the capability to monitor up to two alarm thresholds, with any exceedance signaled by an alert sent to the user.

Key Features

- Wireless transmission of measured values and alarm states
- Battery-powered with low battery indicator (battery life up to 10 years) and external power option
- Remote device configuration via COMET Cloud
- IP65-rated enclosure
- Calibration certificate with declared metrological traceability of standards according to CSN EN ISO/IEC 17025
- Preconfigured Gateway available as an accessory at extra cost. For ease of use, we offer the pre-configured [LoRaWAN Gateway SP041](#), which is fully ready for communication with COMET Cloud and our sensors. This option simplifies the setup process and saves time for users

Technical data

| | |
|---|--|
| TEMPERATURE SENSOR | |
| Measuring range | -30 to +60 °C |
| Accuracy | ±0.4 °C |
| Resolution | 0.1 °C |
| Response time t90 of temperature measurement (temperature step 20°C, air flow approximately 1m/s) | 10 minutes |
| TEMPERATURE SENSOR - external probe Pt1000 | |
| Measuring range | -200 to +260 °C |
| Accuracy | ±0.2 °C in the range -200 to +100 °C; ±0.2 % from reading from +100 to +260 °C |
| Resolution | 0.1 °C |
| Response time t90 of temperature measurement (temperature step 20°C, air flow approximately 1m/s) | 10 minutes |
| GENERAL TECHNICAL DATA | |
| Operating temperature | -30 to +60 °C |

| | |
|-------------------------------|---|
| Channels | internal temperature sensor, 2x external probe P1000 |
| Message transmission interval | adjustable 5-10-15-20-30 minutes, 1-2-3-4-6-8-12-24 hours |
| Operating frequency | Europe 863-870 MHz |
| Maximum transmission power | 25 mW (14 dBm) |
| Typical range of transmitter | 15 km in the field, 2 km in the city (sensor in building) |
| Antenna | internal, gain 2,15 dBi |
| Maximum receiver sensitivity | -136 dBm @BW=125 kHz, SF=12 |
| Power | Lithium battery 3.6 V, AA size |
| Protection class | IP65 |
| Dimensions | 126 x 89 x 40mm |
| Weight (including batteries) | 150g |
| Warranty | 3 years |